



Quality Products. Service Excellence.

Type 1 Mild Steel Splitter Trough *CST Series*

Hinged Door with Screw



Application

- The splitter troughs are designed for distribution of up to 600 A (max) service using either 3 or 4 wires.

Standards

- CSA Certified
- Complies with
 - IEC 60529, IP20

Construction

- Formed and spot welded from 16 gauge steel. When width is 8" or more, 14 gauge.
- Factory installed splitter blocks.
- Series of knockouts on each side.
- Padlocking hasp.

Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.

Accessories

- Splitter Blocks
- Grounding Kits



New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

| 3 Wire Part No. | 4 Wire Part No. | Less Blocks Part No. | CU/AL Amps | Dimensions | | |
|--------------------|--------------------|-------------------------|---------------|------------|------|------|
| | | | | H | W | D |
| CST273 | CST274 | - | 70/70 | 24.00 | 6.00 | 4.00 |
| CST373 | CST374 | - | 70/70 | 36.00 | 6.00 | 4.00 |
| CST473 | CST474 | - | 70/70 | 48.00 | 6.00 | 4.00 |
| CST2103 | CST2104 | CST2100 | 125/120 | 24.00 | 6.00 | 4.00 |
| CST3103 | CST3104 | CST3100 | 125/120 | 36.00 | 6.00 | 4.00 |
| CST4103 | CST4104 | CST4100 | 125/120 | 48.00 | 6.00 | 4.00 |
| CST6103* | CST6104* | CST6100* | 125/120 | 72.00 | 8.00 | 5.00 |
| CST2203* | - | CST2200* | 225/225 | 24.00 | 8.00 | 5.00 |
| CST3203* | CST3204* | CST3200* | 225/225 | 36.00 | 8.00 | 5.00 |
| CST4203* | CST4204* | CST4200* | 225/225 | 48.00 | 8.00 | 5.00 |
| CST5203* | CST5204* | CST5200* | 225/225 | 60.00 | 8.00 | 5.00 |
| CST6203* | CST6204* | - | 225/225 | 72.00 | 8.00 | 5.00 |

| 3 Wire Part No. | 4 Wire Part No. | Less Blocks Part No. | CU/AL Amps | Dimensions H W D | | |
|--------------------|--------------------|-------------------------|---------------|---------------------|-------|------|
| CST3403* | - | CST3400* | 400/340 | 36.00 | 10.00 | 6.00 |
| CST4403* | CST4404* | CST4400* | 400/340 | 48.00 | 10.00 | 6.00 |
| CST5403* | CST5404* | CST5400* | 400/340 | 60.00 | 10.00 | 6.00 |
| CST6403* | CST6404* | CST6400* | 400/340 | 72.00 | 10.00 | 6.00 |
| CST4603* | CST4604* | - | 600/574 | 48.00 | 10.00 | 6.00 |
| CST5603* | CST5604* | - | 600/574 | 60.00 | 10.00 | 6.00 |
| CST6603* | CST6604* | - | 600/574 | 72.00 | 10.00 | 6.00 |

* 14 gauge steel

Data subject to change without notice

© 2019. Hammond Manufacturing Ltd. All rights reserved.